



Scanned by CamScanner



Scanned by CamScanner



Scanned by CamScanner



DUROFLOOR is the latest collection of PVC wooden planks. The shades and designs are carefully chosen to complement the natural wood. Manufactured with multi-layer technology, this premium flooring is highly suitable to handle heavy footfalls. The PUR protection layer ensures trouble free performance and enhance durability. It reduces the noise impact, is trendy, quick to install, easy to use and maintenance free. Finally, Timberland is termite resistant, moisture resistant & Fire resistant. Timberland planks are recommended for hotels, stores, malls, cafeteria, auditorium, schools, banks, homes, offices etc.

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	DUROFLOOR TEST RESULTS
TYPE OF FLOORING	EN 649	RESILIENT FLOORING
THICKNESS	EN 428	1.50 mm
SIZE	EN 427	152.4mm x 914.4mm (6"x 36")
SQUARENESS	EN 427	≤ 0.25 mm
DENSITY	EN 430	3000 gm ²
DIMENSIONAL STABILITY	EN 434	≤ 0.25 mm
RESIDUAL INDENTATION	EN 433	≤ 0.10 mm
FLEXIBILITY	EN 435	No Cracking using 20mm mandre
COLOR FASTNESS	ISO 105 B02	CLASS 6
SLIP RESISTANCE	DIN 51130	R9
BEARING A CASTOR CHAIR	EN 425	SUITABLE /CONTINUOUS USE

RMG POLYVINYL INDIA LIMITED

Registered Office: UGSR 4, Ansals Plaza, Sector 1, Vaishali Ghaziabad 201 010, (U.P) INDIA

Authorised Dealer

The Gondals Press Inc.: +91-9811093024